# **TECHNICAL DATA SHEET**



DIC PSAs web page




**回次注述** 1S14A4 E

Thin type Foam Based Double Coated Adhesive Tape

## DAITAC® #84025BLACK

## Construction



## Characteristics

- √ Good adhesion and conformability
- ✓ Moderate tensile strength which gives it excellent workability when laminating.
- ✓ Excellent impact resistance and durability
- √ Good removability
- ✓ Product does not use the 6 restrictive substances of the RoHS Directive.

## Applications

- √ For waterproofing equipment and devices such as mobile electronics.
- √ For bonding rigid materials like reinforced plastic, metal and glass panel

#### Properties

Test item	Condition	Substrate	Unit	#84025BLACK
Thickness	Except release liner	-	μm	250
180 deg. peel strength	Conform to JIS Z0237	SUS (hairline)	N/20mm	18
		ABS	N/20mm	17
Push Out	DIC method	ABS/AC	N/4cm²	140
Static shear	70°C, 0.5kg	SUS (hairline)	hr	24 <
Impact resistance	DIC method 300g	ABS	height[cm]	90
Waterproof (IPX7)	A depth of 1m for 30 min.	Flat-surface	-	Excellent
		Uneven surface(50 $\mu$ m)	=	Excellent

#### Remarks

Foam carrier may contain large bubbles due to manufacturing method.

If you will use this tape for water-proof parts, please inspect there is no bubble in the parts of these tapes.

Size

980mm in max width

50m in length

#### DIC Corp.

Composite Materials Product Div.

https://www.dic-global.com/en/products/adhesive\_tapes