# **TECHNICAL DATA SHEET**



DIC PSAs web page




1F22A5 E Color & Comfort

Permanent / Removable Double Coated Adhesive Tape

# DAITAC® #8616DJ Black(N)

# Construction



Permanent acrylic adhesive

PET film (black)

Acrylic adhesive (Removable)

Antistatic release film liner (50  $\mu$  m)

**X**Outside of a roll

#### Characteristics

- ✓ Light shielding double sided adhesive tape
- √ No use of halogenide compounds
- √ Good reworkability and re-peelable side leave minimal residue.
- ✓ Excellent light shielding properties. Use in many backlighting applications to control light leakage.
- ✓ Anti-static release film that helps prevents powder contamination during processing.
- ✓ Product does not use the 6 restrictive substances of the RoHS Directive.

# Applications

- ✓ For bonding LCD panel to backlight module for various consumer electronics.
- √ For attaching film used around LCD unit

# Properties

Test item	Condition	Substrate	Unit	#8616DJ Black(N)	
				Permanent adhesive side	Removable adhesive side
Thickness	Except release liner	-	mm	0.05	
Transmittance	Conforms to JIS K7105	-	%	< 0.1	
180 deg. peel strength	23°C, 1hr	SUS (hairline)	N/20mm	10	5
		Polarizing Film	N/20mm	9	4
		PC	N/20mm	10	5
Static shear	40°C, 1kg	SUS (hairline)	mm/hr	< 1	< 1

Remarks

Adhesive strength increases over time when bonded. Reworkability may suffer, so please test the product in advance.

Size

1,000mm in max width

50m in length

### DIC Corp.

Composite Materials Product Div.

https://www.dic-global.com/en/products/adhesive\_tapes/