# **TECHNICAL DATA SHEET**



DIC PSAs web page



Permanent / Removable Double Coated Adhesive Tape

## DAITAC® #8616DJ-50-2

#### Construction

Acrylic adhesive (Stronger)

PET Film

Acrylic adhesive (Removable)

Antistatic release film liner (50 μ m)

\*\*Outside of a roll

#### Characteristics

- ✓ Excellent adhesion, reworkability
- √ Good reworkability and re-peelable side leave minimal residue.
- ✓ Anti-static release film that helps prevents powder contamination during processing.
- √ Smoothness and good dimensional stability
- √ Strong tensile strength due to polyester carrier
- ✓ Product does not use the 6 restrictive substances of the RoHS Directive.

#### Applications

- √ For bonding LCD panel to backlight module for various consumer electronics.
- √ For attaching film used around LCD unit

### Properties

Test item	Condition	Substrate	Unit	#8616DJ-50-2	
				Permanent adhesive side	Removable adhesive side
Thickness	Except release liner	-	mm	0.05	
Transmittance	Conforms to JIS K7105	-	%	85 <	
180 deg. peel strength	23°C, 1hr	SUS (hairline)	N/20mm	10	5
		Polarizing Film	N/20mm	9	4
		PC	N/20mm	10	5
Static shear	40°C, 1kg	SUS (hairline)	mm/hr	< 1	< 1

Remarks

Adhesive strength increases over time when bonded. Reworkability may suffer, so please test the product in advance.

Micro air bubbles on the adhesive may cause a cloudy appearance.

Size

1,000mm in max width

50m in length

#### DIC Corp.

Composite Materials Product Div.

https://www.dic-global.com/en/products/adhesive\_tapes.