TECHNICAL DATA SHEET




DIC PSAs web page



Polyimide Film Based Adhesive Tape

DAITAC® PI-025

Construction



Characteristics

- √ Excellent heat resistance
- √ Good flame retardant (UL 510FR certified)
- √ Good die-cutting and lamination workability due to thick liner
- ✓ Product does not use the 6 restrictive substances of the RoHS Directive.

Applications

- √ For high temperature application
- ✓ Insulating for electrical and electronics devices.

Properties

Test item	Condition	Substrate	Unit	PI-025
Thickness	Except release liner	-	mm	0.05
180 deg. peel strength	Conform to JIS Z0237	SUS (hairline)	N/25mm	9.8
		Cu	N/25mm	6
		AL	N/25mm	5
		ABS	N/25mm	9
		PI	N/25mm	9
Static shear	150°C, 1kg	SUS (hairline)	mm/hr	< 2
Insulation	Surface resistance (PET side)	-	Ω	10 ¹⁴ <
	Volume resistance	-	Ω·cm	10 ¹⁴ <
	Insulation breakdown voltage	-	kV	7

Remarks UL510FR certified [File No.E-167390]

Size 980mm in max width 50m in length

DIC Corp.

Composite Materials Product Div.

https://www.dic-global.com/en/products/adhesive_tapes.