

**Waterborne**

**Product name**  
**BURNOCK DNW-5500**

**Description**

BURNOCK DNW-5500 is a water dispersible polyisocyanate hardener. BURNOCK DNW-5500 has excellent dispersibility and stability in water. It is recommended as hardener for crosslinking of waterborne acrylic polyols.

**Applications**

Industrial coatings.  
Protective coatings.  
Wood coatings.  
Hardener for 2K waterborne polyurethane coatings.

**Key features**

Dispersibility in water.  
Stability in water.  
Compatible with main resins.

**Characteristics**

	<b>BURNOCK DNW-5500</b>
<b>Appearance</b>	Clear liquid
<b>Solid content, weight %</b>	79.0 - 81.0
<b>Viscosity, Gardner 25 °C</b>	G - M
<b>NCO content, %</b>	13.0 - 14.0
<b>Solvent</b>	Methoxypropyl acetate

**Storage**

Store in a cool, dry, well-ventilated place at temperature below 25°C.

**Safe handling note**

Refer to SDS for BURNOCK DNW-5500.  
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

220501

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.