

Waterborne

Product name
EPICLON H-502-42W

Description

EPICLON H-502-42W is a waterborne 1K epoxy dispersion for metal coatings. EPICLON H-502-42W has excellent adhesion, water resistance and anti-corrosion properties. It is recommended for anti-corrosion primers on metals.

Applications

Anti-corrosion metal coatings.
Industrial coatings.
Heavy duty.
Marine coatings.

Key features

Can be used as 1K paint without hardener.
Anti-corrosion.
Water resistance.
Pigment dispersibility.
Adhesion.

Characteristics

	EPICLON H-502-42W
Appearance	Milky white liquid
Solids content, weight %	37.0 - 41.0
Viscosity, mPa s	500 - 10000
pH	8.0 - 11.0
Solvent	Water / Butyl cellosolve / Isopropyl alcohol

Storage

Store in a cool, dry, well-ventilated place at temperatures below 25°C.

Safe handling note

Refer to SDS for EPICLON H-502-42W.
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

220501

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.