

Waterborne

Product name
WATERSOL ZHW-1346

Description

WATERSOL ZHW-1346 is a waterborne polyester dispersion to use in combination with amino resins for stoving enamels. WATERSOL ZHW-1346 has excellent pigment dispersibility, adhesion to metals and good workability. It is recommended for automotive basecoats and industrial coatings.

Applications

Automotive basecoats.
Industrial coatings.

Key features

Adhesion to metallic substrates.
Pigment dispersibility.
Workability.

Characteristics

	WATERSOL ZHW-1346
Appearance	Turbid liquid
Solids content, weight %	44.0 - 46.0
Viscosity, mPa s, 25°C	50 - 500
pH	6.5 - 7.1
Solvent	Water, Dipropylene glycol monomethyl ether, Dimethylethanolamine

Storage

Store in a cool, dry, well-ventilated place at temperature below 25°C.

Safe handling note

Refer to SDS for WATERSOL ZHW-1346.
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

231218

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.