

Solventborne

Product name
ALUKIDIR AL-3330

Description

ALUKIDIR AL-3330 is a solventborne acrylic modified alkyd resin that can be used with metal carboxylate driers for air drying coatings. ALUKIDIR AL-3330 has high gloss and excellent chemical resistance. It is recommended for direct-to-metal (DTM) in automotive and general industrial coatings.

Applications

Automotive coatings.
Metal coatings.
Direct to metal (DTM) coatings.

Key features

Adhesion to galvanized steel.
High-gloss.
Chemical resistance.

Characteristics

	ALUKIDIR AL-3330
Appearance	Clear liquid
Solids content, weight %	49.0 - 51.0
Viscosity, Gardner 25°C	R - V
Color, Gardner	3 max.
Acid value on solution, mgKOH/g	5 max.
Solvent	Xylene

Storage

Store in a cool, dry, and well-ventilated place as mentioned in SDS.

Safe handling note

Refer to SDS for ALUKIDIR AL-3330
Please confirm with our sales representative regarding the chemical regulations of intended countries.

221114

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.