Color & Comfort

Solventborne

Product name

ACRYDIC WFU-580

Description

ACRYDIC WFU-580 is a solventborne OH functional acrylic resin to use in combination with polyisocyanates for 2K polyurethane coatings. ACRYDIC WFU-580 has excellent adhesion to plastics and chemical resistance. It is recommended for plastic coatings.

Applications

Plastic coatings.

Key features

Adhesion to plastics.
Chemical resistance.
BTX free.

Characteristics

	ACRYDIC WFU-580
Appearance	Clear liquid
Solids content, weight %	59.0 - 61.0
Viscosity, Gardner 25°C	Z2 - Z5
Color, Gardner	1 max.
Acid value on solution, mgKOH/g	3.0 - 5.0
OH value on solution, mgKOH/g	51.0 - 57.0
Solvent	Butyl acetate

Storage

Store in a cool, dry, well-ventilated place at temperatures below 25°C.

Safe handling note

Refer to SDS for ACRYDIC WFU-580.
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.