

Polyester Film Based Double Coated Adhesive Tape

DAITAC #8616DJ Black(N)

CONSTRUCTION

Tape thickness
50μm



Acrylic pressure-sensitive adhesive(Strong)
Polyester film(16μm Black)
Acrylic pressure-sensitive adhesive(Removable)
Antistatic release film liner(75μm)

CHARACTERISTIC

- Not use halogenide compounds
- Differential type adhesive, strong and removable
- Good removability
- Excellent light-shielding power
- Antistatic release film liner

APPLICATION

Joining LCD panel to back light module for mobile electronic equipment

PROPERTY

| | Unit | # 8 6 1 6 D J Black (N) | |
|--|--------|-------------------------|--------------------|
| | | Strong Adhesive | Removable Adhesive |
| Peel strength at SUS | N/20mm | 10.0 | 5.0 |
| 180° angle Polycarbonate | | 10.0 | 7.5 |
| (JIS Z0237) ABS plate | | 10.0 | 6.5 |
| Acrylic plate | | 10.0 | 6.5 |
| Polyester film | | 10.0 | 5.5 |
| Polyimide film | | 10.0 | 5.5 |
| Holding power(40°C,1kg) | mm/h | 1> | 1> |
| Transmittance of visible ray (JIS K7105) | % | 0.1> | |

STANDARD SIZE

1000mm in max width / 50m in length