


*Toluene and xylene free, and Removability Double Coated Adhesive Tape*

## DAITAC #8810TDR

### LOW VOC Adhesive Tape

UL969 certified [File No.MH-12834]

#### CONSTRUCTION



#### CHARACTERISTIC



- Not use Toluene and Xylene.
- Not use fourteen chemical substances specified by Ministry of Health, Labour and Welfare (Japan).
- Excellent removability from various plastic and metal
- Dimensional stable backing provides excellent stability at tape application
- The six hazardous materials restricted by the RoHS directive are not compounded

#### APPLICATION

- For many kind of parts used in electrical and electronics industry
- For mounting various recyclable materials in the industrial applications

#### PROPERTY

		Unit	# 8 8 1 0 T D R
Peel strength at 180° angle	S U S	N /20mm	15.0
	A B S		16.0
	H I P S		15.0
	P C		16.5
	P C / A B S		16.0
	G l a s s		15.0
Holding power (40°C, 1kg)		mm / hr.	1 >
Adhesive strength at 90° angle and constant stress 23°C, 0.3kg/10mm	S U S	mm / hr.	6
	A B S		15
Removability After 7 days at 60°C · 90%RH	S U S		Good
	P C / A B S		Good
	H I P S		Good
Quantity of toluene		μ g / 100cm <sup>2</sup>	1.4

#### STANDARD SIZE

1 0 0 0 mm in max width / 5 0 m in length