

# TECHNICAL DATA SHEET



DIC PSAs  
web page



1N38A1 E Color & Comfort

Polyester Film Based Double Coated Adhesive Tape

## DAITAC® #86188S

### ■ Construction

	} Acrylic adhesive
	} PET Film
	} Acrylic adhesive
	} Paper release liner
※Outside of a roll	

### ■ Characteristics

- ✓ Adhesive surface is very smooth which give the tape good initial adhesion (wettability)
- ✓ For adding dimensional stability to soft material
- ✓ Product does not use the 6 restrictive substances of the RoHS Directive.

### ■ Applications

- ✓ Suitable for spacer application in peripheral glass panels.
- ✓ For adhesion to foam substrate
- ✓ For bonding cushion material of LCD panel

### ■ Properties

Test item	Condition	Substrate	Unit	#86188S
Thickness	Except release liner	-	mm	0.25
180 deg. peel strength	23°C, 1hr	SUS (hairline)	N/20mm	9
Static shear	40°C, 1kg	-	mm/hr	< 2
Ball tack	Conform to JIS Z0237	-	No.	6

■ **Size**                      980mm in max width                      50m in length

**DIC Corp.**

Composite Solutions BU

[https://www.dic-global.com/en/products/adhesive\\_tapes/](https://www.dic-global.com/en/products/adhesive_tapes/)

Please note that the data provided in this catalog (the "Catalog") is offered for informational purposes only, and serves as an example of previously measured values and not guaranteed values. DIC Corporation ("DIC") does not and shall not guarantee suitability and compatibility of the Products and the materials that the buyer will incorporate the Products with. Please note that prior to any use of the products stated in the Catalog (the "Products"), it is the buyer's responsibility to confirm the suitability and compatibility of the Products and the materials that the buyer will incorporate the Products with. DIC may modify the specifications of the Products stated in the Catalog at any time and at DIC's sole discretion prior to any use of the products. DIC shall not be liable for any infringement on any third parties' intellectual property rights resulting from the Products' existence, sale, use, combination with any materials, or any other applications or the Products thereof. DIC is the owner of the copyright associated with this Catalog. Copying and/or reprinting this Catalog without obtaining prior permission in writing from DIC is strictly prohibited.