TECHNICAL DATA SHEET




2E32A3 E Color & Comfort

PET based black adhesive tape

DAITAC[®] IL-05G

Construction



PET release liner

Acrylic adhesive (Black)

PET Film

XOutside of a roll

Characteristics

- ✓ PET film carrier black adhesive tape
- ✓ Excellent adhesion
- ✓ Good electrical insulating properties.
- ✓ Product does not use the 6 restrictive substances of the RoHS Directive.

Applications

✓ For insulation.

✓ For laminating graphite sheet.

Properties

Test item	Condition	Substrate	Unit	IL-05G
Thickness	Except release liner	-	μ m	5
180 deg. peel strength	23°C, 1hr	SUS (hairline)	N/25mm	3.5
Transmittance	-	-	%	35

Size

1,000mm in max width 100-150m in length

DIC Corp.

Composite Solutions BU

https://www.dic-global.com/en/products/adhesive_tapes/

Please note that the data provided in this catalog (the "Catalog") is offered for informational purposes only, and serves as an example of previously measured values and not guaranteed values. DIC Corporation ("DIC") does not and shall not guarantee suitability and compatibility of the Products and the materials that the buyer will incorporate the Products with. Please note that prior to any use of the products stated in the Catalog (the "Products"). it is the buyer's responsibility to confirm the suitability and compatibility of the Products and the materials that the buyer will incorporate the Products with. DIC may modify the specifications of the Products stated in the Catalog at any time and at DIC's sole discretion prior to any use of the products. DIC shall not be liable for any infringement on any third parties' intellectual property rights resulting from the Products' existence, sale, use, combination with any materials, or any other applications or the Products thereof. DIC is the owner of the copyright associated with this Catalog. Copying and/or reprinting this Catalog without obtaining prior permission in writing from DIC is strictly prohibited.