# **TECHNICAL DATA SHEET**



DIC PSAs web page



Polyester Film Based Adhesive Tape

## DAITAC® PF-075H

### Construction



#### Characteristics

- √ Good heat resistance, weathering resistance.
- ✓ Excellent adhesion, stability.
- ✓ Good electrical insulating properties.
- ✓ Product does not use the 6 restrictive substances of the RoHS Directive.

#### Applications

√ For some industrial material, insulation.

#### Properties

Test item	Condition	Substrate	Unit	PF-075H
Thickness	Except release liner	-	mm	0.11
180 deg. peel strength	Conform to JIS Z0237	SUS (hairline)	N/25mm	17.6
		PET	N/25mm	17.2
		ABS	N/25mm	16.7
		PC	N/25mm	17.2
		PP	N/25mm	13.7
Static shear	70°C, 0.5kg	SUS (hairline)	mm/hr	< 2
Ball tack	Conform to JIS Z0237	-	No.	4
Insulation	Surface resistance (PET side)	-	Ω	$10^{14} <$
	Volume resistance	-	Ω·cm	10 <sup>14</sup> <
	Insulation breakdown strength	-	kV/mm	96

Remarks

PET film is UL94 VTM-2 certified

Size

1,000mm in max width

50m in length

DIC Corp.

Composite Solutions BU

https://www.dic-global.com/en/products/adhesive\_tapes/