

Solventborne

Product name
Idekyd-4608

Description

Idekyd-4608 is a solventborne medium oil alkyd resin to use in combination with polyisocyanates for 2K polyurethane coatings. Idekyd-4608 has high gloss and non-yellowing properties. It is recommended for wood coatings.

Applications

Wood coatings.

Key features

Yellowing resistance.
High gloss.
Hardness.

Characteristics

	Idekyd-4608
Appearance	Clear liquid
Solids content, weight %	58.0 - 62.0
Viscosity, mPa s 23°C	1500 - 3000
Color, Gardner	5 max.
Acid value on solids, mgKOH/g	9 max.
OH value on solids, mgKOH/g	160 - 170
OH content on solids, %	4.8 - 5.2
Type of oil	Castor
Oil length, %	48
Solvent	Xylene

Storage

Store in a cool, dry, and well-ventilated place as mentioned in SDS.

Safe handling note

Refer to SDS for Idekyd-4608.

Please confirm with our sales representative regarding chemical regulatory status of intended countries.

220501

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.