

Solventborne

Product name
Idester-2265

Description

Idester-2265 is a solventborne saturated polyester resin to use in combination with amino resins for stoving enamels. Idester-2265 has excellent hydrolysis resistance and adhesion to polyurethane foam. It is recommended for coil coating backcoats.

Applications

Coil coating backcoats.

Key Features

Hydrolysis resistance.
Adhesion to polyurethane foam.

Characteristics

	Idester-2265
Appearance	Clear liquid
Solids content, weight %	63.0 - 67.0
Viscosity, Gardner (25°C)	X - Z
Color, Gardner	1 max.
Acid value on solids, mgKOH/g	10 max.
OH value on solids, mgKOH/g	130 - 150
Solvent	Solvent-150 / Butyl cellosolve

Storage

Store in a cool, dry, and well-ventilated place as mentioned in SDS.

Safe Handling Note

Refer to SDS for Idester-2265
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

220519

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.