

Permanent / Removable Double Coated Adhesive Tape

# DAITAC #8612DFT(100)

## **CONSTRUCTION**

Tape
Thickness
0. 10mm

Permanent acrylic adhesive
Polyester film 12μm
Removable acrylic adhesive
Paper release liner

### **CHARACTERISTIC**

- Differential adhesive type (permanent / removable)
- Excellent rework-ability

#### **APPLICATION**

- For mounting various recyclable materials in the industrial applications
- For mounting commercial display

#### **PROPERTY**

		unit	#8612DFT (100)	
			Permanent	Removable
Peel adhesion at	SUS	N /20mm	11. 0	10.0
180° angle	РC		10.0	10.0
	ABS		10.0	10.0
	A C		10.0	10.0
Removality	SUS			Good
(60°C, 90%RH, 12days)	РC			Good
	ABS			Good
	A C			Good
Holding power (40°C, 1kg)	)	mm∕hr	2 >	2 >
Ball tack		No.	8	13

STANDARD SIZE

9 8 0 mm in max width / 5 0 m in length

**DIC Corporation** Application Materials Div. http://www.dic-global.com/en/

Items mentioned in this information are for customers' reference and limited to certain examples although they are based on the most reliable data obtained by our company. It is hoped that customers make the best use of these products after careful examination. Concerning to use and processing the products on this documents, it is not guaranteed a industrial ownerships of a third party. All recipes and processes should be modified, if necessary to conform with particular application.